

What is claimed is:

ap

1. A storage disk, comprising:
a disk sector having a beginning and operable to store data; and
a servo wedge located at the beginning of the sector and operable to identify
the sector in conjunction with an initial positioning of a read-write head and
a read of the data from or write of the data to the disk sector.

2. The storage disk of claim 1 wherein:
the sector includes a track that is operable to store the data; and
the servo wedge is operable to identify the track during an initial positioning of a
read-write head and during a subsequent read of the data from or write of
the data to the track.

ap

3. A storage disk, comprising:
data sectors;
servo wedges each identifying a respective data sector; and
no spin-up wedges.

4. The storage disk of claim 3 wherein:
the data sectors comprise tracks; and
each servo wedge identifies and is located in a respective track.

5. A storage disk, comprising:
disk sectors operable to store data;
servo wedges located in the disk sectors and each having a pre-synchronization-
mark section with substantially the same bit pattern and length as the
preambles of the other servo wedges; and

no servo wedge having a pre-synchronization-mark section with a significantly different bit pattern or a significantly different length as compared to the preambles of the other servo wedges.

5 6. The storage disk of claim 5 wherein:
the disk sectors comprise tracks; and
the servo wedges are located in the tracks.

7. The storage disk of claim 5 wherein the pre-synchronization-mark sections
10 of the servo wedges lack erase fields.

ap

8. A storage disk, comprising:
disk sectors operable to store data;
servo wedges located in the disk sectors and having respective location
15 identifiers, position bursts, and other portions, the other portions of each
servo wedge substantially the same as the other portions of all the other
servo wedges; and
no servo wedge having other portions that are significantly different than the
respective other portions of the other servo wedges.

9. The storage disk of claim 8 wherein the other portions of each servo
wedge include a preamble.

10. The storage disk of claim 8 wherein the others portions of each servo
25 wedge include a servo synchronization mark.

11. The storage disk of claim 8 wherein the others portions of each servo
wedge include a servo address mark.

12. The storage disk of claim 8 wherein the location identifier of each servo wedge is different from the location identifier of another servo wedge.

13. The storage disk of claim 8 wherein the position bursts of each servo wedge are different from the position bursts of another servo wedge.

14. A disk-drive system, comprising:

ap a data-storage disk having a surface, data sectors at respective locations of the surface, and servo wedges that each include respective servo data that identifies the location of a respective data sector;

a motor coupled to and operable to rotate the disk;

a read head operable to generate a read signal that represents the servo data and having a position with respect to the surface of the data-storage disk;

a read-head positioning circuit operable to move the read head over the surface of the disk; and

a servo circuit coupled to the read head and to the read-head positioning system, the servo circuit including,

a servo channel operable to recover the servo data from the read signal, and

a processor coupled to the servo channel and operable to detect one of the servo wedges while or after the disk attains an operating speed but before the servo channel recovers servo data from any other of the servo wedges.

15. The disk-drive system of claim 14 wherein:

the servo channel is operable to recover the servo data from the detected servo wedge; and

the servo circuit is operable to,

determine an initial position of the read head from the recovered servo data, and provide the initial position to the read-head positioning circuit.

16. The disk-drive system of claim 14 wherein the servo channel is operable to recover the servo data from the detected servo wedge and to provide the location of the respective data sector to the read-head positioning circuit.

5 17. The disk-drive system of claim 14 wherein:
the servo channel is operable to recover the servo data from the detected servo wedge
and to provide the location of the respective data sector to the read-head
positioning circuit; and
the read-head positioning circuit is operable to determine an initial position of the read
10 head from the location of the respective data sector.

18. The disk-drive system of claim 14 wherein the read-head position circuit
and the servo circuit are unable to determine the position of the read head before the
processor detects the one servo wedge.

15 19. The disk-drive system of claim 14 wherein the read head comprises a
read-write head.

20 *ap* 20. A disk-drive system, comprising:
a data-storage disk having a surface, a data sector at a location of the surface, and a
servo wedge including servo data that identifies the location of the data sector;
a motor coupled to and operable to rotate the disk;
a read head operable to generate a read signal that represents the servo data and
having a position with respect to the surface of the data-storage disk;
25 a read-head positioning system operable to move the read head over the surface of the
disk; and
a servo circuit coupled to the read head and to the read-head positioning system, the
servo circuit including,
a servo channel operable to recover the servo data from the read signal before or
30 during a read of and before or during a write to the data sector, and

a processor coupled to the servo channel and operable to detect the servo wedge while or after the disk attains an operating speed but before the servo channel recovers any servo data.

5 21. The disk-drive system of claim 20 wherein:
the servo channel is operable to recover the servo data from the read signal in response
to the processor detecting the servo wedge; and
the servo circuit is operable to,
determine an initial position of the read head from the servo data recovered in
10 response to the processor detecting the servo wedge, and
provide the initial position to the read-head positioning circuit.

15 22. The disk-drive system of claim 20 wherein:
the servo channel is operable to recover the servo data from the read signal in
response to the processor detecting the servo wedge; and
the servo circuit is operable to provide the location of the data sector to the
read-head positioning circuit.

20 23. The disk-drive system of claim 20 wherein:
the servo channel is operable to recover the servo data from the read signal in
response to the processor detecting the servo wedge;
the servo circuit is operable to provide the location of the data sector to the read-head
positioning circuit; and
the read-head positioning circuit is operable to determine an initial position of the read
25 head from the location of the data sector.

30 24. The disk-drive system of claim 20 wherein the read-head position circuit
and the servo circuit are unable to determine the position of the read head before the
processor detects the one servo wedge.

20

25. A method, comprising:

5 writing a servo wedge onto a surface of a data-storage disk to define a disk sector that is operable to store file data, the servo wedge including servo data that is operable to identify the disk sector during an initial positioning of a head over the disk and during a read of file data from or a write of file data to the disk sector; and

writing (no spin-up wedge) that is solely operable to provide head-location information during the initial positioning of the head.

10

26. The method of claim 25 wherein writing the servo wedge comprises writing the servo wedge at the beginning of the disk sector.

15

27. The method of claim 25 wherein writing the servo wedges comprises writing the servo wedge in a track of the disk sector, the servo data operable to identify the track during an initial positioning of the head and during a read of file data from or write of file data to the track.

20

28. The method of claim 25 wherein writing no spin-up wedge comprises writing no erase field.

met

29. A method, comprising:

25 writing a first servo wedge onto a surface of a data-storage disk to define a first disk sector that is operable to store file data, the first servo wedge including first servo data that is operable to identify the first disk sector during an initial positioning of a head over the disk and during a read of file data from or a write of file data to the first disk sector; and

30

writing a second servo wedge onto the surface of the data-storage disk to define a second disk sector that is operable to store file data, the second servo wedge including second servo data that is operable to identify the second disk sector during a read of file data from or a write of file data to the second disk sector.

30. The method of claim 29 wherein the second servo data is operable to identify the second disk sector during the initial positioning of the head over the disk.

- 5 31. The method of claim 29 wherein the second servo data is unable to identify the second disk sector during the initial positioning of the head over the disk.

09093877 110504
T050T 482560